

New power supply for Strong family of follow spots

An extremely compact and light-weight electronic ballast offers high performance in a small package. Heavy-duty construction handles “trouping” like a pro with recessed controls and easy protected access to the MS and twist lock connectors.

The new B3 2000 Watt ballast is compatible with most Strong xenon followspots. Sized to fit into existing road cases, the B3 is a perfect upgrade or replacement ballast.

Optionally the B3 is available with a three conductor power pig tail for non- twist lock applications and international use.

FEATURES

- Reduced inrush current promotes long lamp life
- Low DC Ripple
- Brown-out protection
- High efficiency and power factor correction
- Thermal over temperature protection
- Current adjustment via easy-access heavy duty potentiometer
- Auto-range 200-250 VAC 50/Hz operation
- LED status indicators
- Light weight
- Solid two piece construction
- Convenient carrying handle

SPECIFICATIONS

Output Class:	2000 Watt Xenon	Power Requirement:	200 - 250 VAC 50/60 Hz
Output Range 2000W:	1600W - 2000W	AC Current 2000W:	Nominal 13 A @ 208 VAC single phase only
DC Current 2000W	65 - 80A	Weight 2000W:	33 lbs (15kg)
Output Voltage 2000W:	23 - 27 VDC	Dimensions 2000W:	19 x 13 x 8 (48cm x 33cm x 20cm)
Indicators:	Power Input, Running	Controls:	Output Power Adjustment