

## *New power supply for Strong family of follow spots*



An extremely compact and light-weight electronic ballast offers high performance in a small package. Heavy-duty construction handles “trouping” like a pro with recessed controls and easy protected access to the MS and twist lock connectors.

The new B3 - 4K ballast is compatible with most Strong xenon followspots. Sized to fit into existing road cases, the B3 - 4K is a perfect upgrade or replacement ballast.

The B3 - 4K is available in two configurations. A three phase input L15-30 twistlock power inlet (208V AC 60 Hz) or single phase (200 - 250 V AC 50/60 Hz) input with a three conductor power pig tail for non-twist lock applications and international use.

## **FEATURES**

- Reduced inrush current promotes long lamp life
- Low DC ripple for stable lamp operation
- Brown-out protection
- High efficiency and power factor correction
- Thermal over temperature protection
- Current adjustment via easy-access heavy duty potentiometer
- Auto-range 200-250 VAC 50/Hz operation
- LED status indicators
- Light weight
- Solid two piece construction
- Convenient carrying handle

## **SPECIFICATIONS**

Output Class:	4000 Watt Xenon	Power Requirement:	200 - 250 V AC 50/60 Hz - single phase, 208 V AC 60 HZ three phase
Output Range:	2500W - 4000W	AC Input:	Nominal 24A @ 240 VAC single phase, 14A @ 208 VAC three phase
DC Current:	80 - 160A	Weight:	63 lbs (28.6kg)
Output Voltage:	25 - 31 VDC	Dimensions:	19 x 18 x 8.5 (48cm x 46cm x 22cm)
Indicators:	Power Input, Running	Controls:	Output Power Adjustment