

An Entirely New Concept



The iChip Mystere offers cutting edge performance in a lightweight, flexible package. Made in the USA to Strong Lighting's exacting standards, it features an aluminum housing and chassis, a variable focal length lens system, and a mechanical dowser and iris. Inside the iChip is a whole new deal. The revolutionary 200 watt multi-LED light engine module is clean and super bright utilizing a unique 36 element micro lens. Aligned with iChip's high quality, coated optics, the LED Module delivers unmatched brightness and a beautiful, crisp, even field.

Weighing in at a mere 60 pounds (with standard tripod stand) and measuring only 28.5" in length, the revolutionary iChip Mystere sets a new standard. At 50' in spot mode, it can produce an impressive 390 fc of daylight-bright illumination. These are output numbers usually associated with arc lamp based follow spots. Yet the iChip uses no heavy, expensive ballast and has no high voltage of UV hazards. It produces a high intensity 5600K beam of flicker free light through its long 6000 hour life.

The Mystere is quiet, energy efficient and cool to the touch. It is a perfect fit for applications where compact size and flexibility are needed. A full featured theater follow spot, it still fits easily into the trunk or the backseat of a care, making it ideal for rental shops, touring, school, church or community groups.

FEATURES

- Small, rugged and compact
- 200W operation
- 5600° K Color Temperature
- 90 CRI
- Six-Color Color Changer with color filters
- Easy to Operate and Maintenance free
- Manual Dimming Control
- Zoom beam adjustment range of 5° to 9°
- Nichrome Steel Iris
- Collapsible, Adjustable-Height Floor Stand with Tilt and Pan Friction Controls
- State-of-art electronic power supply

SPECIFICATIONS

Source:	185 Watt Replaceable LED	Color Module:	Six position color changer
Lamp Life:	6000 hours	Color Filter:	Standard 9"
Color Temperature:	5600°K	Power Requirement:	7A 120VAC 4A 240VAC
CRI:	90	Construction:	Powder-Coated Aluminum
Output	6,650 lumens	Weight(light):	36 lbs (16.3kg)
Useful Throw	15 - 125' (4.5 - 38m)	Weight(stand);	14 lbs (6.3kg)
		Packed weight:	43 lbs (19.5kg)light / 15 lbs (6.8kg)stand
Controls:	On/Fan/Off	Packed Dimensions:	32 x 18 x 20" (81.3 x 45.7 x 50.8cm)
Douser:	Manual "chopper" type	Packed Dimensions:	42 x 19 x 7" (106.7 x 48.3 x 17.8cm)
Zoom:	5° to 9°	Packed Volume:	67 ft ³ (1.9m ³)light / 32.5 ft ³ (.92m ³)stand

PHOTOMETRICS

Based on 185W lamp measured at 50', Flat Field

Narrow Field of View	Throw Distance (Ft/m)	25/7.6	50/15.2	75/23	100/30.5	125/38
	Beam Diameter (Ft/m)	2.3/.70	4.6/1.4	7.0/2.1	9/2.7	11.5/3.5
	Illuminance (fc/lux)	1,600/17,222	400/4,305	173/1,883	100/1,862	64/689
Minimum Diameter Ft/m)		.5/.15	1.0/.30	1.66/.5	2.5/.76	3.0/.91

Wide Field of View	Throw Distance (Ft/m)	25/7.6	50/15.2	75/2.3	100/30.5	na
	Beam Diameter (Ft/m)	4.5/1.37	8/2.44	15.5/4.72	17/5.18	na
	Illuminance (fc/lux)	552/5,942	172/1,851	60/645	46/495	na
Minimum Diameter Ft/m)		.83/.25	1.6/.5	3.2/1.0	4.8/1.5	na

Dimensions

